

## Aluminum Foil Tape AFB2565

### PRODUCT DESCRIPTION

A 25 micron (1.0 mil) high tensile strength aluminum foil backing, combined with a high performance water-based acrylic adhesive, protected by an easy-release silicone release paper.

### FEATURES

- Aluminum backing provides excellent reflection of both heat and light.
- High quality adhesive with strong adhesion and holding power offers permanent sealing and bonding on Foil-Scrim-Kraft Facing joints and seams in HVAC ductwork application.
- Good aging resistance both indoors and outdoors.
- Low moisture vapor transmission rate offers excellent sealing and patching performance.

### TYPICAL PHYSICAL PROPERTIES

PROPERTIES	METRIC	TEST METHOD
Backing Thickness	25 Micron	PSTC-133 / ASTM D 3652
Total Thickness	65 Micron	PSTC-133 / ASTM D 3652
Adhesion to Steel	15 N/25mm	PSTC-101 / ASTM D 3330
Tack Rolling Ball	20cm	PSTC-6 / ASTM D 3121
Tensile Strength	45 N/25mm	PSTC-131 / ASTM D 3759
Elongation	3.0%	PSTC-131 / ASTM D 3759
Applying Temperature	-10°C to +40°C	

### TYPICAL APPLICATIONS:

HVAC industry for joining and sealing Foil-Scrim-Kraft Facing laminated fiberglass blanket / duct board joints and seams; joining and sealing flexible air duct seams and connections. General purpose holding, patching, sealing and masking applications - indoors and outdoors.