

## Self-Wound Aluminum Foil Tape **AFA75125WL**

### PRODUCT DESCRIPTION

A nominal 75 micron release coated aluminum foil backing, combined with a high performance solvent acrylic adhesive. It is Aluminum foil tape without release paper liner.

### FEATURES

- Self-Wound Aluminum Foil Tape makes easy application.
- Aluminum backing provides excellent reflection of both heat and light.
- Good aging resistance both indoors and outdoors.
- Low moisture vapor transmission rate offers excellent sealing and patching performance.

### TYPICAL PHYSICAL PROPERTIES

PROPERTIES	METRIC	TEST METHOD
Backing Thickness	75Micron	PSTC-133 / ASTM D 3652
Total Thickness	125Micron	PSTC-133 / ASTM D 3652
Adhesion to Steel	18N/25mm	PSTC-101 / ASTM D 3330
Tack Rolling Ball	20 cm	PSTC-6 / ASTM D 3121
Tensile Strength	100 N/25mm	PSTC-131 / ASTM D 3759
Elongation	5.0%	PSTC-131 / ASTM D 3759
Service Temperature	-30°C to +120°C	
Applying Temperature	-10°C to +40°C	

### TYPICAL APPLICATIONS:

Excellent for fixing copper tube of Freezers and Refrigerator. General purpose holding, patching, sealing and masking.